

COMET**NEWS**

PATRIOT Series



ELECTRICAL HOT WATER HP CLEANERS
IDROPULITRICI ELETTRICHE AD ACQUA CALDA



140 ÷ 150 bar



420 ÷ 480 l/h

Cleaning is a pleasure when satisfies expectations
Pulire è un piacere quando soddisfa le aspettative



PATRIOT 140












PATRIOT 150 Gold



GENERAL FEATURES / CARATTERISTICHE GENERALI

- Electrical pump with three axial pistons arranged vertically with pump at the bottom and an all-metal construction without any plastic used for the structural components
- Brass head (on Patriot 150 Gold) or aluminum head
- 4 Lt Diesel tank with inlet filter and cap
- EASY-START device
- TotalStop device
- Vertical burner with high thermal efficiency steel coil
- Auxiliary engine for ventilation of boiler unit
- Delayed burner start
- Safety valve
- Boiler thermal protection
- Double switch (cold water - hot water)
- Induction motor with thermal protection
- Elettropompa a tre pistoni assiali disposta in verticale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali
- Testa pompa in ottone (su Patriot 150 Gold) o alluminio
- Serbatoio Diesel da 4 Lt con filtro riempimento e tappo
- Dispositivo EASY-START
- Dispositivo TotalStop
- Caldaia verticale con serpentina in acciaio ad alto rendimento
- Motore ausiliario per ventilazione del gruppo caldaia
- Partenza ritardata del bruciatore
- Valvola di sicurezza
- Protezione termica della caldaia
- Doppio interruttore (acqua fredda - acqua calda)
- Motore ad induzione con protezione termica

MODELS MODELLI	PUMP HEAD TESTATA POMPA												
		Ph	V	Hz	bar	MPa	l/h	kW	°C	l	kg/h	kg	(L x W x H) cm
PATRIOT 140	PT 03	1	230	50	140	14	420	2,1	90	4	2,3	43	58 x 44 x 93
PATRIOT 150 Gold	KLR Gold	1	230	50	150	15	480	2,3	90	4	2,3	43	58 x 44 x 93

STANDARD ACCESSORIES / DOTAZIONE STANDARD

	Gun GH 251 with protection <i>Pistola GH 251 con protezione</i>		Bent lance with protection, without nozzle <i>Lancia angolata con protezione, senza ugello</i>
	Fan shape nozzle 25°, 1/4" MEG connection <i>Ugello con getto a lama 25° attacco 1/4" MEG</i>		8 m rubber delivery hose kit - R1 1/4" <i>Kit tubo gomma mandata 8 m - R1 1/4"</i>
		Foam lance <i>Lancia schiumogena</i>	

OPTIONAL ACCESSORIES / ACCESSORI OPTIONAL

	Gun GH 281 with pressure regulator + Swivel <i>Pistola GH 281 con regolatore pressione + Swivel</i>		Lance with rotating nozzle <i>Lancia con ugello rotante</i>
	Rotating brush (max 60°C) <i>Idrospazzola rotante (max 60°C)</i>		Soda blasting lance <i>Lancia sabbiante</i>
	Drain nozzle (max 60°C) <i>Sonda spurgatubi (max 60°C)</i>		SC 150 floor cleaning lance kit <i>Kit tubo lancia lavapavimenti SC 150</i>
	Antiscale device <i>Dispositivo anticalcare</i>		Rubber delivery hose extension kit <i>Kit prolunga tubo gomma mandata</i>



COMET**NEWS**

Follow us on



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

Comet, Italian Excellence